

WAAS CH 58003 W14A	APP CRS 136°	Rwy Idg 5502 TDZE 583 Apt Elev 583
--	------------------------	---

RNAV (GPS) RWY 14


FREEMAN MUNI (SE.R)

RNP APCH - GPS.


NA Baro-VNAV and VDP NA when using Louisville Muhammad Ali Intl altimeter setting. Rwy 14 helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Louisville Muhammad Ali Intl altimeter setting and increase all DA 117 feet and all MDA 120 feet; increase LPV and LNAV/VNAV all Cats and LNAV and Circling Cats C/D visibility 1/4 SM.

MISSED APPROACH:
Climb to 2400 direct
ZEKAM and hold.

AWOS-3 119.425	LOUISVILLE APP CON 132.075 327.0	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



ELEV 583	TDZE 583
-----------------	-----------------



4 NM Holding Pattern RUYOT		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 24).		2400	ZEKAM
6000 ← 316°		TOLUY 2500		↑	
2600 → 136°		BEGND 3.2 NM to RW14		✧	
GP 3.00° TCH 40		2500 1640			
		6 NM 2.7 NM 2 NM 1.2 NM			
CATEGORY	A	B	C	D	
LPV DA	860-7/8		277 (300-7/8)		
LNAV/VNAV DA	1037-13/8		454 (500-13/8)		
LNAV MDA	980-1	397 (400-1)	980-1 1/8	397 (400-1 1/8)	
CIRCLING	1040-1 457 (500-1)	1100-1 517 (600-1)	1300-2 717 (800-2)	1300-2 1/4 717 (800-2 1/4)	