

APP CRS

301°

Rwy Idg

7504

TDZE

405

Apt Elev

410

RNAV (RNP) Z RWY 30

TRI-CITIES (PSC)

▼

For uncompensated Baro-VNAV systems, procedure NA below -14°C (7°F) or above 54°C (130°F). RF required. GPS required. For inoperative ODALS, increase RNP 0.11 visibility all Cats to 1¼ mile, and increase RNP 0.30 visibility all Cats to 1½ mile.

ODALS

MISSED APPROACH: Climb to 5200 on track 301° to WEDAV, left turn to YOCUY, and on track 254° to PAIDS and hold.

ATIS 125.65	SPOKANE APP CON ★ 128.75 377.2	TRI-CITIES TOWER ★ 135.3 (CTAF) 0 323.3	GND CON 121.8	CLNC DEL 120.0	UNICOM 122.95
----------------	-----------------------------------	--	------------------	-------------------	------------------

ELEV 410	D	TDZE 405		
REIL Rwy 3L and 12 MIRL Rwy 12-30 0 HIRL Rwy 3L-21R 0				
5200 WEDAV tr 301° YOCUY tr 254° PAIDS JIGPI 1900 See planview for multiple IF locations. GP 3.00° TCH 54				
CATEGORY	A	B	C	D
RNP 0.11 DA	778-1⅞ 373 (400-1⅞)			
RNP 0.30 DA	834-1¼ 429 (500-1¼)			
AUTHORIZATION REQUIRED				

PASCO, WASHINGTON

Amtd 1 13NOV14

46°16'N-119°07'W

TRI-CITIES (PSC)

RNAV (RNP) Z RWY 30