

WAAS CH 81918 W22A	APP CRS 221°	Rwy Idg TDZE 164 Apt Elev 170
--	------------------------	---

RNAV (GPS) RWY 22

TUSCALOOSA NTL (TCL)


▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. Helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Birmingham altimeter setting: increase LPV DA to 760 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 937 feet and all visibilities ¾ SM; increase all MDAs 180 feet and visibility LNAV Cats C and D ½ SM and Circling Cat C ¾ SM and Cat D ½ SM. Baro-VNAV and VDP NA when using Birmingham altimeter setting. Circling Rwy 12, 30 NA at night.

MISSED APPROACH: Climb to 2500 direct ROBND and left turn on track 131° to MOVIL and on 050° track to OKW VORTAC and hold.

ASOS 132.825	BIRMINGHAM APP CON 120.15 269.25	TUSCALOOSA TOWER ★ 126.3 (CTAF) 0 256.7	GND CON 121.8 257.95	CLNC DEL 120.775	UNICOM 122.95
------------------------	--	--	--------------------------------	----------------------------	-------------------------



ELEV 170

TDZE 164

221°

4000 X 100

6000 X 150

TWR 236

MIRL Rwy 12-30

HIRL Rwy 4-22

2500

ROBND

MOVIL

OKW

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).

Procedure Turn NA

*LNAV only.

NORLK 3 NM to RW22

UMABE 1800

221°

2300

GP 3.00°

TCH 60

CATEGORY	A	B	C	D
LPV DA	582-1½	418 (500-1½)		
LNAV/VNAV DA	759-2	595 (600-2)		
LNAV MDA	700-1 536 (600-1)	700-1½ 536 (600-1½)	700-1¾ 536 (600-1¾)	
CIRCLING	720-1 550 (600-1)	800-1 630 (700-1)	960-2¼ 790 (800-2¼)	960-2½ 790 (800-2½)