

ILS or LOC RWY 17L
CITY OF COLORADO SPRINGS MUNI (COS)

MISSED APPROACH: Climb to 7200 then climbing left turn to 9000 on heading 020° and on BRK VOR/DME R-091 to ADANE INT/BRK VOR/DME 11.1 DME and hold.

A

7200 9000
↑ hdg 020°
BRK R-091
ADANE
Use I-LPI DME when on the localizer course.
MOGAL INT I-LPI 20.9
ROCK INT I-LPI 10.1
AWONE INT I-LPI 14.4
HUMPE INT I-LPI 6.5
I-LPI 2.4 I-LPI 4.8
8700 7540 8700 9000 10000
172°
GS 3.00° TCH 57
2.4 NM 1.7 NM 2.6 NM 1.2 NM 6.5 NM

CATEGORY	A	B	C	D
S-ILS 17L	6387/18 200 (200-½)			
S-LOC 17L	7540/40 1353 (1400-¾)	7540/55 1353 (1400-1)	7540-3	1353 (1400-3)
C CIRCLING	7540-1¼ 1353 (1400-1¼)	7540-1½ 1353 (1400-1½)	7540-3	1353 (1400-3)
HUMPE FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-LOC 17L	7020/24 833 (900-½)	7020/40 833 (900-¾)	7020-1⅞	833 (900-1⅞)
C CIRCLING	7020-1¼	833 (900-1¼)	7040-2½ 853 (900-2½)	7260-3 1073 (1100-3)

FAF to MAP 7.7 NM					
Knots	60	90	120	150	180
Min:Sec	7:42	5:08	3:51	3:05	2:34