

WAAS
CH **48912**
W32A

APP CRS
319°

Rwy Idg
TDZE **53**
Apt Elev **53**

RNAV (GPS) RWY 32

SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

RNP APCH

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 49°C. When local altimeter setting not received use Georgetown altimeter setting: increase LPV DA to 305 feet; increase LNAV/VNAV DA to 510; increase all MDA 60 feet and LNAV Cat C and Circling Cat D visibility ¼ SM. For inoperative MALSRR, increase LNAV Cat D visibility to 1¼ SM. VDP and Baro-VNAV NA when using Georgetown altimeter setting.

MALSRR

MISSED APPROACH:
Climb to 2100 direct HYDRS and hold.

ASOS 118.325	PATUXENT APP CON★ 127.95 314.0	SALISBURY TOWER★ 119.425 (CTAF) 0	GND CON 123.775	CLNC DEL 123.775	CLNC DEL 132.45 (when twr closed)	UNICOM 122.95
------------------------	--	---	---------------------------	----------------------------	--	-------------------------

ELEV 53		TDZE 53	
2100 HYDRS		*LNAV only	
COLBE		FRYER	
PUJKE 2 NM to RW32		4 NM Holding Pattern	
RW32		2000	
1 NM		6.1 NM	
CATEGORY		A	
LPV DA		253-½ 200 (200-½)	
LNAV/VNAV DA		458-1 405 (500-1)	
LNAV MDA		420-½ 367 (400-½)	
CIRCLING		480-1 427 (500-1)	
		520-1 467 (500-1)	
		560-1½ 507 (600-1½)	
		700-2 647 (700-2)	

SALISBURY, MARYLAND

Amtd 2A 25MAR21

SALISBURY-OCEAN CITY WICOMICO RGNL (SBY)

38°20'N-75°31'W

RNAV (GPS) RWY 32