

LOC/DME I-BRO
110.3
Chan 40

APP CRS
132°

Rwy Idg **7399**
TDZE **19**
Apt Elev **22**

ILS or LOC RWY 13

BROWNSVILLE/SOUTH PADRE ISLAND INTL (BRO)

ADF or RADAR required.

▼

VDP NA when using Port Isabel altimeter setting. For inop ALS increase S-LOC 13 Cats C and D visibility to 1 3⁄8 miles. When local altimeter setting not received, use Port Isabel altimeter setting and increase DA to 307 feet and all MDA 40 feet. S-LOC 13 Cat C and D visibility to RVR 5500, Circling Cat D visibility to 2 1⁄4 miles. For inop ALS when using Port Isabel altimeter setting increase S-LOC 13 Cats C/D visibility to 1 3⁄8 miles.

MALSR

AS

MISSED APPROACH:
Climb to 700 then climbing left turn to 2000 direct HRL VOR/DME and hold.

ATIS 128.55	VALLEY APP CON 119.5 257.6	BROWNSVILLE TOWER ★ 118.9 (CTAF) 239.3	GND CON 121.9	UNICOM 122.95
-----------------------	--------------------------------------	--	-------------------------	-------------------------

1049 A

312°

177°

357°

2000

1900

199°

177°

RELAX

HARLINGEN 113.65 HRL Chan 83 (Y)

LOM/IAF DEPOO 393 BR

I-BRO 7.3

1900 to LOM 287° (8.1)

BROWNSVILLE 116.3 BRO Chan 110

ALTERNATE MISSED APCH FIX

DEPOO 393 BR I-BRO 7.3

LOCALIZER 110.3 I-BRO Chan 40

UNITED STATES MEXICO

MSA BR 25 NM

2600 1600

539 A

179 A

117 A

180 A

312°

132°

Remain within 10 NM

DEPOO LOM I-BRO 7.3

700 2000 HRL

1900 312° 1848 1900 132°

GS 2.75° TCH 58

*I-BRO 2.8 I-BRO 1.4 *LOC only.

4.6 NM 1.4 NM

CATEGORY	A	B	C	D
S-ILS 13		269/24	250 (300-1⁄2)	
S-LOC 13	480/24	461 (500-1⁄2)	480/50	461 (500-1)
CIRCLING	480-1 458 (500-1)	540-1 518 (600-1)	540-1 1⁄2 518 (600-1 1⁄2)	680-2 658 (700-2)

MIRL Rwy 18-36
HIRL Rwy 13-31

FAF to MAP 6 NM

Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00

BROWNSVILLE, TEXAS

Orig-B 20JUN19

BROWNSVILLE/SOUTH PADRE ISLAND INTL (BRO)

25°54'N-97°26'W

ILS or LOC RWY 13