

|                                        |                        |                                                   |             |
|----------------------------------------|------------------------|---------------------------------------------------|-------------|
| WAAS<br>CH <b>82512</b><br><b>W05A</b> | APP CRS<br><b>054°</b> | Rwy Idg<br>TDZE <b>439</b><br>Apt Elev <b>439</b> | <b>6051</b> |
|----------------------------------------|------------------------|---------------------------------------------------|-------------|

RNAV (GPS) RWY 5

MADISONVILLE RGNL (2I0)

RNP APCH - GPS.

▼

▲

Baro-VNAV and VDP NA when using EVV altimeter setting. Rwy 5 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use EVV altimeter setting and increase LPV DA to 788 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 818 feet and all visibilities ⅛ SM; increase all MDAs 100 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH:  
Climb to 2600 direct LOREE and hold.

|                          |                                              |                          |                                 |
|--------------------------|----------------------------------------------|--------------------------|---------------------------------|
| AWOS-3<br><b>126.475</b> | EVANSVILLE APP CON ★<br><b>124.025 290.9</b> | CLNC DEL<br><b>120.1</b> | UNICOM<br><b>122.7 (CTAF) 0</b> |
|--------------------------|----------------------------------------------|--------------------------|---------------------------------|

