

LOC I-MQY <u>111.1</u>	APP CRS 321°	Rwy Idg 8038 TDZE 518 Apt Elev 543
----------------------------------	------------------------	---

ILS or LOC RWY 32
SMYRNA (MQY)

DME required.


T
A NA Circling Rwy 14 NA at night. DME from BNA VORTAC, simultaneous reception of I-MQY and BNA DME required. For Inop ALS, increase S-LOC 32 Cats C/D visibility to 1 SM.

MALS R




MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 on heading 060° and on BNA VORTAC R-104 to WORDU/ BNA 18.6 DME and hold.

AWOS-3PT 119.125	NASHVILLE APP CON 118.4 360.7	SMYRNA TOWER ★ 118.5 (CTAF) 0 233.1	GND CON 121.4	CLNC DEL 121.4	CLNC DEL 121.7 (When twr closed)	UNICOM 122.95
----------------------------	---	---	-------------------------	--------------------------	---	-------------------------



ELEV	543		TDZE	518
------	-----	--	------	-----



REIL Rwy 14 **L**
HIRL Rwy 14-32 **L**
MIRL Rwy 1-19 **L**
REIL Rwy 1, 19, and 32

1500 ↑	3000 hdg 060°	BNA R-104	WORDU BNA 18.6	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 57).			
				OXCUH BNA 16.5	JOPIV INT BNA 23.8	One Minute Holding Pattern	
CATEGORY	A		B		C		D
S-ILS 32	718-1½ 200 (200-½)						
S-LOC 32	900-½ 382 (400-½)		900-5⁄8		382 (400-5⁄8)		
CIRCLING	1100-1 557 (600-1)		1180-1 637 (700-1)		1260-2 717 (800-2)		1480-3 937 (1000-3)

ILS or LOC RWY 32