

|                                        |                        |                                        |                                         |
|----------------------------------------|------------------------|----------------------------------------|-----------------------------------------|
| WAAS<br>CH <b>45508</b><br><b>W36A</b> | APP CRS<br><b>002°</b> | Rwy Idg<br>TDZE<br>Apt Elev <b>407</b> | <b>8000</b><br><b>401</b><br><b>407</b> |
|----------------------------------------|------------------------|----------------------------------------|-----------------------------------------|

RNAV (GPS) RWY 36

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Evansville altimeter setting. When local altimeter setting not received, use Evansville altimeter setting: increase LPV DA to 656 feet; increase LNAV/VNAV DA to 720 feet and all Cats visibility 1/8 mile; increase all MDA 60 feet and LNAV Cats C/D and Circling Cats C/D visibility 1/4 mile.

MALSR

MISSED APPROACH:

Climb to 3000 direct HUMAD and hold.

|                            |                                              |                                                   |                         |                         |
|----------------------------|----------------------------------------------|---------------------------------------------------|-------------------------|-------------------------|
| AWOS-3PT<br><b>119.025</b> | EVANSVILLE APP CON ★<br><b>124.025 290.9</b> | OWENSBORO TOWER ★<br><b>120.7 (CTAF) 0 251.15</b> | GND CON<br><b>121.7</b> | UNICOM<br><b>122.95</b> |
|----------------------------|----------------------------------------------|---------------------------------------------------|-------------------------|-------------------------|

MISSED APCH FIX

30 NM to ECOCO

3000

ECOCO

092° 272°

4 NM Holding Pattern

ECOCO

COPOM

XIXIH 2.5 NM to RW36

3000

HUMAD

GP 3.00° TCH 56

\*1240

\*1 NM to RW36

RW36

\*LNAV only.

ELEV 407

D

TDZE 401

MIRL Rwy 6-24

HIRL Rwy 18-36

REIL Rws 6, 18, and 24

| CATEGORY     | A                    | B                     | C                     | D                             |
|--------------|----------------------|-----------------------|-----------------------|-------------------------------|
| LPV DA       |                      | 601-1/2               | 200 (200-1/2)         |                               |
| LNAV/VNAV DA |                      | 665-1/2               | 264 (300-1/2)         |                               |
| LNAV MDA     | 780-1/2              | 379 (400-1/2)         | 780-5/8               | 379 (400-5/8)                 |
| CIRCLING     | 860-1<br>453 (500-1) | 1120-1<br>713 (800-1) | 1140-2<br>733 (800-2) | 1140-2 1/4<br>733 (800-2 1/4) |

OWENSBORO, KENTUCKY

OWENSBORO/DAVIESS COUNTY RGNL (OWB)

Amdt 4B 25MAR21

37°44'N-87°10'W

RNAV (GPS) RWY 36