

## MAYNR THREE DEPARTURE (RNAV)

**TOP ALTITUDE:  
ASSIGNED BY ATC**



RNAV 1 - DME/DME/IRU or GPS.  
From SLIPT to MAXIM: RNAV 1- GP  
From SLIPT to CANOA: RNAV 1- G

RADAR required for non-GPS equipped aircraft.  
RADAR required.

## TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500' /NM to 1300.  
 Rwy 9R: Standard with minimum climb of 500' /NM to 1500.  
 Rwy 13: Standard with minimum climb of 500' /NM to 1800.  
 Rwy 27L: Standard with minimum climb of 500' /NM to 1900.  
 Rwy 27R: Standard with minimum climb of 500' /NM to 1700.  
 Rwy 31: Standard with minimum climb of 500' /NM to 1400.

NOTE: Jet aircraft only.  
NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

MSA MB 25 NM

29

FL180  
1300  
185°  
(34)



FL180

FL18\*  
1300  
(15)

MAXIM

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 12 JUN 2025 to 10 JUL 2025

MAYNR THREE DEPARTURE (RNAV)  
(MAYNR3.MAYNR) 31OCT24

MIAMI, FLORIDA  
MIAMI EXEC (TMR)

31 OCT 24