

ALAMOGORDO, NEW MEXICO

HI-RNAV (GPS) RWY 22

APCH CRS	Rwy Idg	10,578
218°	TDZE	4083
	Arprt Elev	4093

- (USAF)

HOLLOMAN AFB (KHMN)

RNP APCH-GPS	ALSF-1	MISSED APPROACH: Climb to 5000 then climbing right turn to 7000 direct JOBAM and hold.
* When ALS inop, increase vis to 1 ¼ miles. ** When ALS inop, increase CAT AB vis to 1 mile; CAT CDE vis to 1 3/8 miles.		

ATIS★ 273.5	ALBUQUERQUE CENTER 132.65 257.6	APP CON 120.6 269.225	TOWER★ 119.3 254.4	GND CON 127.05 275.8	CLNC DEL 126.7 289.4
----------------	------------------------------------	--------------------------	-----------------------	-------------------------	-------------------------

*** When Circling to Rwy 25 at Night, operational VGSI required, remain on or above VGSI glidepath until threshold. Circling Visibility Reduction by Helicopters NA.

Visibility reduction by helicopters NA.

INBOUND WEST: Airspace West Restricted. Expect routing via CORONA.

Unlit terrain 4083' MSL 200' from threshold, 400' right of course.

Unlit terrain 4083' MSL 200' from threshold, 72' right of course.

For uncompensated Baro-VNAV systems, procedure NA below -23°C (-9°F) or above 54°C (129°F). Average Cold Temperature based on standard -30.00°C ISA deviation.

CAUTION: High terrain to the East within 15 NM.

CAUTION: Circling to Rwy 4 NA at night.

CAUTION: When Rwy 16 VGSI inop, circling to Rwy 16 NA at night.

When VGSI inop, procedure NA at night.

USAF Only: When VGSI inop, straight-in Rwy 22 authorized at night with aircrew command approval.

CAUTION: CAT E and portions of CAT D circling not fully contained in controlled airspace.

5 NM

HOLD 10,000 7000

JOBAM

COPOR 10,200

DACAG 10,000

(IF) LEVAK

DANLE

(FAF) CIMVU

JOGDI

4298

RW22

4255

5000

7000

9000

9695

MSA RW22 2.5 NM

1,100

(IAF) KASTL 11,000

NOT FOR CIVIL USE

EMERG SAFE ALT 100 NM 14,200

5000

7000

JOBAM

↑

↷

✦

RW22

1.3 NM to RW22

JOGDI

CIMVU

DANLE

LEVAK

4900

5700

6800

7600

2.5 NM

2.5 NM

GP 3.00°

TCH 52

218°

CATEGORY	A	B	C	D	E
LNAV/VNAV DA*	4507-¾		424	(500-¾)	
LNAV MDA**	4540-½ 457 (500-½)		4540-⅞	457	(500-⅞)
CIRCLING***	4620-1 527 (600-1)		4660-1½ 567 (600-1½)	5200-3 1107 (1200-3)	5300-3 1207 (1300-3)

ELEV 4093

TDZE 4083

218°

91

25

34

0.3% DOWN

10,928 x 300

TWR 4171

12,924 x 150

0.3% UP

HIRL all Rwys

REIL Rwy 22

SW-1, 12 JUN 2025 to 10 JUL 2025

SW-1, 12 JUN 2025 to 10 JUL 2025