

RADAR INSTRUMENT APPROACH MINIMUMS

ALBUQUERQUE, NM

Amdt 21, 29MAY14 (14149) (FAA)

ELEV 5355

ALBUQUERQUE INTL SUNPORT (ABQ)

RADAR-1 123.9 127.4 253.5 354.1 

	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS
ASR	8		AB	5700/24	385	(400-½)	CDE	5700/35	385	(400-¾)
	3		AB	5700/24	395	(400-½)	CDE	5700/35	395	(400-¾)
 CIRCLING	ALL RWYS		A	5840-1	485	(500-1)	B	5920-1	565	(600-1)
			C	5920-1½	565	(600-1½)	DE	6460-3	1105	(1200-3)

CAUTION: Steeply rising terrain in the northeast quadrant exceeding 8000 at 8 NM from airport and in southeast quadrant exceeding 6300 at 4.6 NM from airport.
Circling Category E not authorized southeast of Rwy 3-21 and northeast of Rwy 12-30.
For inoperative MALSR, increase S-3 and S-8 CAT E visibility to RVR 6000.

12 JUN 2025 to 10 JUL 2025

ROSWELL, NM

Orig-D, 06OCT22 (22279) (FAA)

ELEV 3671

ROSWELL AIR CENTER (ROW)

RADAR-1 119.6 239.0 

	RWY	GP/TCH/RPI	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS	CAT	DA/ MDA-VIS	HAT/ HAA	CEIL-VIS
ASR	21 ¹		AB	4040-½	407	(500-½)	C	4040-¾	407	(500-¾)
			DE	4040-1	407	(500-1)				
	3		ABC	4020-1	353	(400-1)	DE	4020-1¼	353	(400-1¼)
	17		AB	4080-1	414	(500-1)	C	4080-1½	414	(500-1½)
			DE	4080-1¼	414	(500-1¼)				
	35		ABC	4060-1	389	(400-1)	D	4060-1¼	389	(400-1¼)
			E	4060-1½	389	(400-1½)				
CIRCLING	ALL RWYS		AB	4140-1	469	(500-1)	C	4140-1½	469	(500-1½)
			D	4300-2	629	(700-2)	E	4400-2½	729	(800-2½)

¹For inoperative MALSR, increase CAT D visibility to 1¼, and CAT E visibility to 1½.
Procedure NA when ROW ATCT closed.

12 JUN 2025 to 10 JUL 2025

RADAR INSTRUMENT APPROACH MINIMUMS